

TECHNICAL DATA SHEET

Smart•Therm® Induction Charger

Application

The ideal Induction Charging System for room service, meal delivery, and boosting applications. Space efficient. Operates only when used in conjunction with Dinex® bases.

Construction

The charger is manufactured in the United States and constructed with the main body of stainless steel and a high strength surface. The charger is equipped with a microprocessor that performs unique automatic standby/ shut-off functions and incorporates a proprietary automatic sensor for use with Dinex® Induction Bases. A visible Information Center displays the portion of the charge that has been completed, user prompts, operational status, and error conditions.

Standard Features

- Countertop design, stainless steel housing, heavy duty electronic components, and high strength top, engineered for use in commercial kitchens.
- User-friendly buttons for power control.
- Boost feature provides a method to pre-charge bases in preparation for periods of high demand, then boost to increase throughput at the Charging Station.
- A visible display using LCD technology with an Information Center and an audible alert.
- Display easily converted to other languages. (French, Spanish, English)
- Automatic standby/shut-off feature.
- Attractive, tough, and easy-to-clean tempered glass surface is impact and heat resistant.
- Integral fan system keeps internal electronics cool.
- Dedicated (208/240) 1-phase connection.
- Base cycle time approximately 16 to 20 seconds.
- Space efficient 13.7" x 18.5" footprint.
- Washable filter.
- Internal surge protection.
- Twist lock plug- NEMA L6-20P.

Smart•Therm® System

- Automatically senses both Smart•Therm® bases (DX8210 series) and Dinex® DuraTherm® bases (DX1411 series) and gives the precise amount of energy to achieve the correct temperature on every charge.
- Microprocessor monitors vital components and runs near continuous performance checks
- Charger shuts off automatically and displays "error codes" in plain text enabling the user to identify minor problems.
- Uses durable Dinex® Induction Bases

Smart•Therm® - Product Numbers

- DX811220 (208V/240V) 1-Phase

Bases for Induction System

- DX821003 – Onyx
- DX821050 – Blue
- DX821044 – Graphite Grey
- DX821061 – Cranberry
- DX821084 – Sage
- DX821031 – Latte

Replacement Filter for Induction

- DXPLE9560 - Dinex® Induction Filter 4.8"

Drying & Storage Racks for Induction Bases

- DXIBDRS90 - Holds 90 Induction Bases
- DXIBDRS180 - Holds 180 Induction Bases
- DXIBDRS270 - Holds 270 Induction Bases

Warranty

Two years parts and labor.



NEMA L6-20P



TECHNICAL DATA SHEET

Smart•Therm® Induction Charger

Item Number	Model Number	Overall Size			Electrical Specifications			Shipping Specs	
		W	D	H	Volts	AMPS	Watt	Ship Weight	Ship Cube
DX811220	811220	13.66" (34.7cm)	18.5" (47cm)	5.41" (13.74cm)	208v/240v 1-Phase	16	3350/3850	26 lbs.	1.9

